

Dell Wyse 3050



Performance

Operating System

Dell Wyse ThinOS™

Processor

Marvell ARMADA PXA 510 v7 1.0 GHz system-on-chip (SoC)

Memory

1GB Flash / 1GB RAM DDR3

Power

Worldwide auto-sensing 100-240 VAC, 50/60 Hz
Energy Star V5.0
Phase V external and EuP compliant power adapter

Power consumption

Under 7.2 Watts (average)

Security

Built-in Kensington security slot (cable sold separately)

Certifications

Certifications (Based on US ratings)

Citrix Ready,

I/O peripheral support

One DVI-I port, DVI to VGA (DB-15) adapter included

S

One DVI-D port

N/A

Dual display support with optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately)

S

Four USB 2.0 ports

S

SD Card Slot

S

Networking

Networking

10/100/1000 Base-T Gigabit Ethernet
Optional internal wireless 802.11 b/g/n

Display

VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate

S

Single monitor

1920x1200@60Hz; color depth: 24 bpp

Dual monitors

Up To 1920x1080@60Hz; color depth: 24 bpp

Audio

Output: 1/8-inch mini jack, full 16-bit stereo, 48KHz sample rate

S

Input: 1/8-inch mini jack, 8-bit microphone

S

Composite audio jack: 1/8-inch mini, 16-bit stereo

N/A

Dimensions

Height x Width x Depth

25mm x 177mm x 119 mm (1 inch x 6.9 inches x 4.69 inches)

Weight

451 g (1 lb)

Mountings

Horizontal stand and VESA/wall mounting

S

Vertical stand

AO

Temperature Range

Horizontal position

10° to 35° C (50° to 95° F)

Vertical position, button up

10° to 40° C (50° to 104° F)

Storage

-10° to 60° C (14° to 140° F)

Humidity

Condensing

20% to 80%

Non-condensing

10% to 95%

Included

Enhanced USB keyboard with PS/2 mouse port and Windows keys

S

PS/2 or USB optical mouse included (varies by region)

S

Warranty

3-year limited hardware warranty

S